

Cinch-Koaxialkabel für dynamischen Audioklang

Wer Wert auf guten Klang legt, benötigt die richtigen Audiokabel. Weil elektromagnetische Wechselwirkungen die empfindlichen Audiosignale schnell beeinflussen können, helfen die mehrfach geschirmten Kabel den feinen Impulsen dabei, unverfälscht bis zum Verstärker zu gelangen. Reine Materialien und die präzise Verarbeitung unterstützen dies zusätzlich.

- **75 Ω definierter Wellenwiderstand**
- **reine Kupferleiter und 2-fach Schirmung für klare Signalqualität**
- **24-Karat vergoldete Kontakte für minimale Übertragungswiderstände**

Technische Daten


Anschlüsse	
Steckermaterial:	3-fach umspritztes PVC / ABS
Kontaktmaterial:	24-Karat-vergoldet
Schirmung:	ja
Anschluss 1, Typ:	CINCH-Stecker (RCA)
Anschluss 1, Steckerlänge (mm):	39,8
Anschluss 1, Steckerbreite (mm):	14,0
Anschluss 1, Steckerhöhe (mm):	14,0
Anschluss 2, Typ:	CINCH-Stecker (RCA)
Anschluss 2, Steckerlänge (mm):	39,8
Anschluss 2, Steckerbreite (mm):	14,0
Anschluss 2, Steckerhöhe (mm):	14,0

Kabel	
Typ:	Rundkabel
Länge (m):	0,5 1 2 3 5 7,5 10 15 20
Material Innenleiter:	OFC (sauerstofffreies Kupfer)
Durchmesser Innenleiter (mm):	25 x 0,120
AWG:	23
Anzahl Schirmungen:	2 x
Typ 1. Schirmung:	Aluminium-Folie
Typ 2. Schirmung:	Kupfer-Geflecht 96 Adern x 0,12 mm Querschnitt
Material Außenmantel:	hochelastisches PVC
Durchmesser Außenmantel (mm):	6,0
Knickschutz:	beidseitig


Signalübertragung	
Übertragungsarten:	analoge und digitale Audiosignale
max. Bandbreite (MHz):	10,0
Kapazität (pF):	155
Wellenwiderstand (Ω):	75

Allgemein	
Betriebstemperatur von / bis (°C):	-10 / +80
Garantie (Jahre):	10

casual












Kabelquerschnitt



Schaltplan



Artikelnr.	Kabellängen (m)	Verpackung (Maße in mm)	Gewicht (kg)	Abbildung	EAN Code
70442	0.50	Einzelkarton: 185 x 80 x 25 Export VPE (40 Stk.): 400 x 295 x 235	Einzelkarton: 0.07 Export VPE: 4.00		4 040849 704420
70443	1.00	Einzelkarton: 185 x 80 x 25 Export VPE (40 Stk.): 400 x 295 x 235	Einzelkarton: 0.09 Export VPE: 5.10		4 040849 704437
70445	2.00	Einzelkarton: 185 x 80 x 35 Export VPE (30 Stk.): 400 x 270 x 235	Einzelkarton: 0.14 Export VPE: 5.30		4 040849 704451
70446	3.00	Einzelkarton: 185 x 180 x 40 Export VPE (24 Stk.): 400 x 285 x 435	Einzelkarton: 0.23 Export VPE: 6.90		4 040849 704468
70447	5.00	Einzelkarton: 185 x 180 x 40 Export VPE (24 Stk.): 400 x 285 x 435	Einzelkarton: 0.32 Export VPE: 8.90		4 040849 704475
70448	7.50	Einzelkarton: 185 x 180 x 55 Export VPE (20 Stk.): 400 x 310 x 435	Einzelkarton: 0.45 Export VPE: 11.00		4 040849 704482
70449	10.0	Einzelkarton: 185 x 180 x 55 Export VPE (20 Stk.): 400 x 310 x 435	Einzelkarton: 0.55 Export VPE: 12.30		4 040849 704499
70451	15.00	Einzelkarton: 185 x 180 x 75 Export VPE (16 Stk.): 400 x 335 x 435	Einzelkarton: 0.77 Export VPE: 14.30		4 040849 704512
70452	20.00	Einzelkarton: 185 x 180 x 75 Export VPE (16 Stk.): 400 x 335 x 435	Einzelkarton: 0.99 Export VPE: 17.10		4 040849 704529

TARIC-Code: 85444290900

Bei Clicktronic® werden alle Kabel oberhalb einer Länge von 7,5 Metern gemäß der Testkriterien als Standard HDMI™-Kabel bezeichnet, auch wenn sie ursprünglich als High Speed HDMI™-Kabel ausgelegt wurden und ggf. auch über größere Distanzen eine deutliche Mehrleistung zeigen.

Alle enthaltenen Firmennamen und Produktbezeichnungen sind Warenzeichen der jeweiligen Inhaber. Alle Rechte vorbehalten. Bei HDMI™ handelt es sich um eine eingetragene Marke der HDMI Licensing L.L.C.

Der Inhalt kann von den Abbildungen abweichen. Druckfehler und Änderungen an Produkt, Verpackung oder Dokumentation behalten wir uns vor. Clicktronic®, Pillmannstraße 12, D-38112 Braunschweig

Audio cable

cinch coaxial cable for dynamic audio sound

When you value good sound, you will need the right audio cable. Because electromagnetic interactions can easily affect sensitive audio signals, multiple shielded cables assist subtle pulses to be undistorted up to the amplifier. Pure materials, and precise workmanship render additional support.

- 75 Ω defined wave impedance
- pure copper conductor and 2-way shielding for clear signal quality
- 24-Karat gold plated contacts for minimum transfer resistances

Specifications

Connections

Plug material:	triple-coated PVC / ABS
Contact material:	24-Karat gold plated
Shielding:	yes
Port 1, type:	RCA plug (RCA)
Connector 1, connector length (mm):	39.8
Connector 1, connector width (mm):	14.0
Connector 1, connector height (mm):	14.0
Port 2, type:	RCA plug (RCA)
Connector 2, connector length (mm):	39.8
Connector 2, connector width (mm):	14.0
Connector 2, connector height (mm):	14.0

cable

Type:	Round cable
Length (m):	0.5 1 2 3 5 7.5 10 15 20
Inner conductor material:	OFC (Oxygen free copper)
Inner conductor diameter (mm):	25 x 0.120
AWG:	23
Number of shieldings:	2 x
Type of 1st shielding	Aluminium foil
Type of 2nd shielding	Copper braid 96 wires x 0.12 mm cross section
Outer sheath material:	highly elastic PVC
Outer sheath diameter (mm):	6.0
Kink protection:	on both sides

Signal transmission

Transmission modes:	analog and digital audio signals
max. Bandwidth (MHz):	10.0
Capacitance (pF):	155
Characteristic impedance (Ω):	75

General

Operating temperature from / to (°C):	-10 / +80
Warranty (years):	10

clicktronic®

entertainment.
pure.


casual




RCA plug (RCA)



RCA plug (RCA)



Cross section



Wiring diagram



Designed in Germany

10 Years Warranty
High-Quality Assurance










OFC
99.99% Oxygen Free Copper

24 Carat Gold
Anti Resistance Connections

2x
Cable Shielding

Audio cable

cinch coaxial cable for dynamic audio sound

Article no.	Cable lengths (m)	Packaging dimensions (mm)	Weight (kg)	Figure	EAN Code
70442	0.50	Single carton: 185 x 80 x 25 Master carton (40 pcs.): 400 x 295 x 235	Single carton: 0.07 Master carton: 4.00		4 040849 704420
70443	1.00	Single carton: 185 x 80 x 25 Master carton (40 pcs.): 400 x 295 x 235	Single carton: 0.09 Master carton: 5.10		4 040849 704437
70445	2.00	Single carton: 185 x 80 x 35 Master carton (30 pcs.): 425 x 270 x 235	Single carton: 0.14 Master carton: 5.30		4 040849 704451
70446	3.00	Single carton: 185 x 180 x 40 Master carton (24 pcs.): 400 x 285 x 435	Single carton: 0.23 Master carton: 6.90		4 040849 704468
70447	5.00	Single carton: 185 x 180 x 40 Master carton (24 pcs.): 400 x 285 x 435	Single carton: 0.32 Master carton: 8.90		4 040849 704475
70448	7.50	Single carton: 185 x 180 x 55 Master carton (20 pcs.): 400 x 310 x 435	Single carton: 0.45 Master carton: 11.00		4 040849 704482
70449	10.0	Single carton: 185 x 180 x 55 Master carton (20 pcs.): 400 x 310 x 435	Single carton: 0.55 Master carton: 12.30		4 040849 704499
70451	15.00	Single carton: 185 x 180 x 75 Master carton (16 pcs.): 400 x 335 x 435	Single carton: 0.77 Master carton: 14.30		4 040849 704512
70452	20.00	Single carton: 185 x 180 x 75 Master carton (16 pcs.): 400 x 335 x 435	Single carton: 0.99 Master carton: 17.10		4 040849 704529

TARIC Code: 85444290900

At Clicktronic® cables are designated as standard HDMI™ cables above a length of 7.5 meters, according to the test criteria, even if they originally are designed as High Speed HDMI™ cables and mostly show a significant power increase over long distances.

All company and product names are trademarks of their respective owners. All rights reserved. HDMI™ is a registered trademark of HDMI Licensing L.L.C.

The content may differ from those shown. We reserve the right for printing errors and changes to product packaging or documentation. Clicktronic®, Pillmannstraße 12, D-38112 Braunschweig/Germany