



cable printing: 1007 E41396  AWM VW-1 80°C 300V PACIFICA-CSA TR 64 LL30603 FTI 80°C -F-



P1	P2
1 	1, 2, 3
2 	4, 5, 6
4 	7, 8, 9
3 	10, 11, 12

Power-Adapter

- Verbinder: 4pol. St. > 15pol. S-ATA Winkelbuchse
- Innenleiter: 18AWG
- Isolierung: PVC
- Schirmung: ungeschirmt
- Kontaktwiderst.: max. 30hm
- Isolationswid.: min. 20MOhm
- Gewicht: 9g
- RoHS-konform

USB 2.0 Hi-Speed cable

- Connectors: 4-pin 5.25 power plug > 15-pin S-ATA angled jack
- Inner conductor: 18AWG
- Insulation: PVC
- Shielding: unshielded
- Contact resist.: max. 30hms
- Insulation res.: min. 20MOhms
- Weight: 9g
- RoHS compliant

Änderungen

Änderungen		Datum	Name	Bezeichnung	Blatt
Datum	Name	gez.: 14.08.2014	tf	CAK SATA 4P/S-ATA POWER 90° up	
		gepr.: 14.08.2014	tf		
		Norm:		Zeichnungs-Nr.: 93030	von
Änderungen vorbehalten / Subject to change					